POWERLOK RACK PDU SPECIFICATION



Specific Configurations

COLOR	CARBON		RED		WHITE		BLUE	
WHIP LENGTH	6 FT	10 FT	6 FT	10 FT	6 FT	10 FT	6 FT	10 FT
SWITCHED READY MODEL	**PL8607S-06WC**	**PL8607S-10WC**	**PL8607S-06WR**	**PL8607S-10WR**	**PL8607S-06WW**	**PL8607S-10WW**	**PL8607S-06WB**	**PL8607S-10WB**
MONITORED MODEL	**PL8607M-06WC**	**PL8607M-10WC**	**PL8607M-06WR**	**PL8607M-10WR**	**PL8607M-06WW**	**PL8607M-10WW**	**PL8607M-06WB**	**PL8607M-10WB**
BASIC MODEL	**PL8607B-06WC**	**PL8607B-10WC**	**PL8607B-06WR**	**PL8607B-10WR**	**PL8607B-06WW**	**PL8607B-10WW**	**PL8607B-06WB**	**PL8607B-10WB**
DESCRIPTION	RACK PDU, 72”, 60A 208/240V DELTA 3PH, 36-C13 & 6-C19, IEC 309 (IP67), CORDLOK, TAA COMPLIANT							
POWER	60A 208/240V DELTA 3PH (17.2 kW)							
PLUG TYPE	IEC 309 (IP67) WATERTIGHT							
UNIT LENGTH	72 INCHES							
RECEPTACLES	36-C13 & 6-C19							
CORD LOCK	YES							

Universal Specification

Power Input	See Ratings Table - page 2
Over Current Protection	None
Chassis	Heavy duty corrosion resistant steel, powder coat per specific configuration for color
Mounting Method	Tool-less vertical rack-mount, 61.25” button center spacing
Manufacturing location	USA
Product Warranty	7-year from date of shipment, repair or replace
Certification/Agency Approvals	TUV Certified to UL62328-1, CSA C22.2, NOM Addendum for Mexico, FCC Part 15 Class A conformance, RoHS compliant
Operating Environment	0-60C (32-149F), 5-95% relative humidity, 0-10,000ft (0-3000 meters) elevation
Storage Environment	-25-65C (-13-149F), 5-95% relative humidity, 0-10,000ft (0-3000 meters) elevation
Chassis Dimensions (LxWxD)	72.0”L x 2.18”W x 2.0”D
Package Dimensions (LxWxD)	80.0”L x 22.0”W x 4.8”D (3&4-Pack), 80.0”L x 11.0”W x 4.8”D (1&2-Pack)
Pallet Dimensions (LxWxD)	82”L x 44”W x 5.0”D
Rack PDU Weight	18.3 lbs.
Packaged Weight (each)	20.3 lbs.
Monitored & Switched Ready Versions	
Monitoring Types	Monitored models: Remote & local touchscreen display, temp/humidity sensor ready & Switched Ready models with added capability to pair switching cords with rPDU.
Monitoring Accuracy	Voltage: +/- 0.5% at nominal, current: within 0.5% from 1A to 30A typical. +/1% of measurement from 500mA to 30A
Total Unit & Group Monitoring	Aggregate (kWh, W, VA) plus Phase: A, B, C Line Currents, plus Group: 1, 2, 3 Monitoring (kWh, W, VA, PF, V, A)
Network Interface	Ethernet RJ-45, 10 Mbit/s, 100 Mbit/s, 1 Gbit/s
Transport/Internet	TCP/IP v4, v6
Network Applications	HTTP/HTTPS Webserver RESTful API, SNMP-V1/V2c/V3, Modbus TCP/IP Network Management DHCP for dynamic IP address request from a server on the network Remote firmware upgrade using FTP
Touchscreen Digital Display	Touch to rotate, touch to view: power data, rPDU and environment temps, and admin. screens
Internal Voltage & Current Sensors	RMS method for accuracy
Environmental Monitoring	Optional temp/humidity sensor daisy chain (up to 4 sensors), monitoring accuracy +/- 0.2C and +/- 2% Rh

MADE AND ROBOTICALLY SOLDERED IN THE USA

POWERLOK

*CUSTOMER SIGNATURE:	DATE:	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MM AND TOLERANCES ARE: X = +/- 0.5 .X = +/- 0.25 .XX = +/- 0.13 X° = +/- 0.5°	Gateview Technologies, Inc.	
*PRIOR TO MANUFACTURING, CUSTOM MODELS REQUIRE CUSTOMER SIGN-OFF. BY SIGNING, CUSTOMER AGREES THAT THIS ORDER IS NON-CANCELABLE AND NON-RETURNABLE.			TITLE: **RACK PDU SPECIFICATION**	
			DRAWING NUMBER: **SP-PL8607X**	SHEET: **1 OF 2**

THIS SPECIFICATION AND ITS CONTENTS ARE THE PROPERTY OF GATEVIEW AND SHALL NOT BE COPIED OR REPRODUCED FOR ANY PURPOSES OTHER THAN APPLICATION OF PRODUCT MANUFACTURED BY GATEVIEW. THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE.

OUTLINE DRAWING









DETAIL A

PLUG/OUTLETS

SEE CONFIGURATION TABLE FOR ACTUAL PLUG & OUTLETS

IEC 60309 3P4W IP44 SPLASHPROOF
60A/250V 48A DERATED INPUT



IEC 60309 3P4W IP67 WATERTIGHT
60A/250V 48A DERATED INPUT



IEC 60320 C13 10A/250V
INTL. & 15A/250V N.A.
MAX RATED OUTPUT

IEC 60320 C19 16A/250V
INTL. & 20A/250V N.A.
MAX RATED OUTPUT

NEMA L6-30R . 30A/250V
MAX RATED OUTPUT

PDU WIRING DIAGRAM & RATINGS TABLE



FOR MONITORED VERSIONS ONLY. CT1-A - CT3-B NOT ON BASIC MODELS.

INPUT POWER:	
WHIP TYPE	6GA 4-WIRE SOOW TYPE W
VOLTAGE	208/240V DELTA 3PH
FREQUENCY	50/60 HZ
RATED AMPS	60A
MAX CONT.AMPS	48A
OUTPUT POWER:	
GROUP 1A	PH A-N, 16A MAX CONT.
GROUP 2A	PH B-N, 16A MAX CONT.
GROUP 3A	PH C-N, 16A MAX CONT.
GROUP 1B	PH A-N, 16A MAX CONT.
GROUP 2B	PH B-N, 16A MAX CONT.
GROUP 3B	PH C-N, 16A MAX CONT.

MADE AND ROBOTICALLY SOLDERED IN THE USA

POWERLOK

*CUSTOMER SIGNATURE:	DATE:	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MM AND TOLERANCES ARE: X = +/- 0.5 .X = +/- 0.25 .XX = +/- 0.13 X° = +/- 0.5°	Gateview Technologies, Inc.
*PRIOR TO MANUFACTURING, CUSTOM MODELS REQUIRE CUSTOMER SIGN-OFF. BY SIGNING, CUSTOMER AGREES THAT THIS ORDER IS NON-CANCELABLE AND NON-RETURNABLE.			TITLE: **RACK PDU SPECIFICATION**
			DRAWING NUMBER: **SP-PL8607X** / SHEET: **2 OF 2**

THIS SPECIFICATION AND ITS CONTENTS ARE THE PROPERTY OF GATEVIEW AND SHALL NOT BE COPIED OR REPRODUCED FOR ANY PURPOSES OTHER THAN APPLICATION OF PRODUCT MANUFACTURED BY GATEVIEW. THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE.