

POWERLOK RACK PDU SPECIFICATION

Specific Configuration

DESCRIPTION	RACK PDU, 88”, 125A 208/240V DELTA 3PH, 6-C13 & 24-C19, PHASE COLOR CORDLOK, TAA COMPLIANT							
POWER	125A 208/240V DELTA 3PH (36.0 kW)							
RECEPTACLES	LOCKING: 6-C13 & 24-C19							
UNIT LENGTH	88 INCHES							
COLOR	CARBON		RED		WHITE		BLUE	
WHIP LENGTH	6 FT	10 FT	6 FT	10 FT	6 FT	10 FT	6 FT	10 FT
INPUT PLUG & MODELS:								
HUBBELL POWERGAIN™ HBL4125P250								
SWITCHED READY	**PL9063S-06FC**	**PL9063S-10FC**	**PL9063S-06FR**	**PL9063S-10FR**	**PL9063S-06FW**	**PL9063S-10FW**	**PL9063S-06FB**	**PL9063S-10FB**
MONITORED INPUT	**PL9063V-06FC**	**PL9063V-10FC**	**PL9063V-06FR**	**PL9063V-10FR**	**PL9063V-06FW**	**PL9063V-10FW**	**PL9063V-06FB**	**PL9063V-10FB**
BASIC	**PL9063B-06FC**	**PL9063B-10FC**	**PL9063B-06FR**	**PL9063B-10FR**	**PL9063B-06FW**	**PL9063B-10FW**	**PL9063B-06FB**	**PL9063B-10FB**
HUBBELL POWERGAIN™ HBL200MR SINGLE POLE								
SWITCHED READY	**PL9063S-06SC**	**PL9063S-10SC**	**PL9063S-06SR**	**PL9063S-10SR**	**PL9063S-06SW**	**PL9063S-10SW**	**PL9063S-06SB**	**PL9063S-10SB**
MONITORED INPUT	**PL9063V-06SC**	**PL9063V-10SC**	**PL9063V-06SR**	**PL9063V-10SR**	**PL9063V-06SW**	**PL9063V-10SW**	**PL9063V-06SB**	**PL9063V-10SB**
BASIC	**PL9063B-06SC**	**PL9063B-10SC**	**PL9063B-06SR**	**PL9063B-10SR**	**PL9063B-06SW**	**PL9063B-10SW**	**PL9063B-06SB**	**PL9063B-10SB**
WHIP ONLY, NO PLUG								
FOR HARDWIRING, ALL MODELS ARE AVAILABLE WITH WHIPS TO A SPECIFIED LENGTH AND NO PLUGS. CONTACT US FOR DETAILS.								

Universal Specification

Over Current Protection	Quantity (12) 20A UL489 magnetic hydraulic breakers
Chassis	Heavy duty corrosion resistant steel, powder coat per specific configuration for color
Mounting Method	Tool-less vertical rack-mount, 61.25” button center spacing
Manufacturing location	USA
Product Warranty	7-year from date of shipment, repair or replace
Certification/Agency Approvals	TUV Certified to UL62328-1, CSA C22.2, NOM Addendum for Mexico, FCC Part 15 Class A conformance, RoHS compliant, BAA options available
Operating Environment	0-60C (32-149F), 5-95% relative humidity, 0-10,000ft (0-3000 meters) elevation
Storage Environment	-25-65C (-13-149F), 5-95% relative humidity, 0-10,000ft (0-3000 meters) elevation
Chassis Dimensions (LxWxD)	78.0”L x 2.9”W x 2.0”D, 2.90”D
Package Dimensions (LxWxD)	86.0”L x 22.0”W x 4.8”D (3&4-Pack), 96.0”L x 11.0”W x 4.8”D (1&2-Pack)
Pallet Dimensions (LxWxD)	96”L x 44”W x 5.0”D
Rack PDU Weight	39 lbs. - varies by whip length
Packaged Weight (each)	41 lbs. - varies by whip length

Monitored & Switched Ready Versions

Monitoring Types	Monitored models: Remote & local touchscreen display, temp/humidity sensor ready & Switched Ready models with added capability to pair switching cords with rPDU.
Monitoring Accuracy	Voltage: +/- 0.5% at nominal, current: within 0.5% from 1A to 30A typical. +/1% of measurement from 500mA to 30A
Total Unit & Group Monitoring	Aggregate (kWh, W, VA) plus Phase: A, B, C Line Currents, plus Group: 1, 2, 3 Monitoring (kWh, W, VA, PF, V, A)
Network Interface	Ethernet RJ-45, 10 Mbit/s, 100 Mbit/s, 1 Gbit/s
Transport/Internet	TCP/IP v4, v6
Network Applications	HTTP/HTTPS Webserver RESTful API, SNMP-V1/V2c/V3, Modbus TCP/IP Network Management DHCP for dynamic IP address request from a server on the network Remote firmware upgrade using FTP
Touchscreen Digital Display	Touch to rotate, touch to view: power data, rPDU and environment temps, and admin. screens
Internal Voltage & Current Sensors	RMS method for accuracy
Environmental Monitoring	Optional temp/humidity sensor daisy chain (up to 4 sensors), monitoring accuracy +/- 0.2C and +/- 2% Rh

MADE AND ROBOTICALLY SOLDERED IN THE USA

POWERLOK

*CUSTOMER SIGNATURE:	DATE:	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MM AND TOLERANCES ARE: X = +/- 0.5 .X = +/- 0.25 .XX = +/- 0.13 X° = +/- 0.5°	GATEVIEW TECHNOLOGIES, INC.	
*PRIOR TO MANUFACTURING, BUILD MODELS REQUIRE CUSTOMER SIGN-OFF. BY SIGNING, CUSTOMER AGREES THAT THIS ORDER IS NON-CANCELABLE AND NON-RETURNABLE.			TITLE: **RACK PDU SPECIFICATION**	
			DRAWING NUMBER: **SP-PL9063X**	SHEET: **1 OF 2**

THIS SPECIFICATION AND ITS CONTENTS ARE THE PROPERTY OF GATEVIEW AND SHALL NOT BE COPIED OR REPRODUCED FOR ANY PURPOSES OTHER THAN APPLICATION OF PRODUCT MANUFACTURED BY GATEVIEW. THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE.

OUTLINE DRAWING



DETAIL A

PDU RATINGS TABLE

INPUT POWER:			
WHIP TYPE	2 AWG 4-WIRE SOOW TYPE W		
VOLTAGE	208/240V DELTA 3PH		
FREQUENCY	50/60 HZ		
RATED AMPS	125A		
MAX CONT.AMPS	100A		
MAXIMUM CONTINUOUS OUTPUT POWER:			
GROUP 1A	PH A-B, 16A	GROUP 1C	PH A-B, 16A
GROUP 2A	PH B-C, 16A	GROUP 2C	PH B-C, 16A
GROUP 3A	PH C-A, 16A	GROUP 3C	PH C-A, 16A
GROUP 1B	PH A-B, 16A	GROUP 1D	PH A-B, 16A
GROUP 2B	PH B-C, 16A	GROUP 2D	PH B-C, 16A
GROUP 3B	PH C-A, 16A	GROUP 3D	PH C-A, 16A

INPUT / PLUG OPTIONS - 3P4W

SEE CONFIGURATION TABLE FOR ACTUAL.

HUBBELL POWERGAIN
HBL4125P250 125A/250V



HUBBELL POWERGAIN
HBL200MR SINGLE POLE 200A/250V



PLUG HOUSING COLOR

OUTPUT CONNECTOR OPTIONS

SEE CONFIGURATION TABLE FOR ACTUAL.

IEC 60320 C19
16A/250V, 20A/250V N.A.



IEC 60320 C13
10A/250V, 15A/250V N.A.

NEMA L6-30R
30A/250V

PDU WIRING DIAGRAM



MONITORING ONE-LINE

FOR MONITORED VERSIONS ONLY.



CT QUANTITY DETERMINED BY MODEL VARIATION

MADE AND ROBOTICALLY SOLDERED IN THE USA

POWERLOK

*CUSTOMER SIGNATURE:	DATE:	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MM AND TOLERANCES ARE: X = +/- 0.5 .X = +/- 0.25 .XX = +/- 0.13 X° = +/- 0.5°	GATEVIEW TECHNOLOGIES, INC.
*PRIOR TO MANUFACTURING, BUILD MODELS REQUIRE CUSTOMER SIGN-OFF. BY SIGNING, CUSTOMER AGREES THAT THIS ORDER IS NON-CANCELABLE AND NON-RETURNABLE.			TITLE: **RACK PDU SPECIFICATION**
			DRAWING NUMBER: **SP-PL9063X** / SHEET: **2 OF 2**

THIS SPECIFICATION AND ITS CONTENTS ARE THE PROPERTY OF GATEVIEW AND SHALL NOT BE COPIED OR REPRODUCED FOR ANY PURPOSES OTHER THAN APPLICATION OF PRODUCT MANUFACTURED BY GATEVIEW. THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE.